



## WT1012M 1 CHANNEL REWORK KIT, 95 W, 230 V

ORDER NO: T0053460699

COMPACT. POWERFUL. VERSATILE.  
BOOST YOUR PRODUCTIVITY

### Discover the WT 1M Soldering Station, your ultimate productivity partner.

With extremely fast heat-up and recovery times, it handles all tasks effortlessly. No more juggling tools or compromising performance – just reliable versatility and unmatched value. Choose worry-free precision and unstoppable productivity. Choose Weller WT Soldering Stations.

## + KEY FEATURES

#### > 1 CHANNEL REWORK KIT (95 W)

to cover micro and standard soldering and desoldering tasks including WTMT MS Micro tweezers with active (cartridge) tip technology

#### > RTW TIP FAMILY

5 seconds heat-up time

#### > HIGH PRODUCTIVITY

#### > INTUITIVE USE

thanks to clear menu structure

#### > REDUCED FOOTPRINT

thanks to stackability

#### > GRAPHICAL BACKLIT LC-DISPLAY

#### > HIGH PERFORMANCE AND FUNCTIONALITY

many connectable tools

#### > HOUSING COVER

useable as storage

#### > OFF TIME, PROCESS WINDOW,

Lock function, Offset Stackable units

#### > CONNECTABLE TO

ZeroSmog Fume Extraction Units

#### > STATION SET

to cover smallest to standard rework tasks

#### > MICRO DESOLDERING TOOLS

with active (cartridge) tips 5 seconds heat-up time

#### > STACKABLE UNITS

with active (cartridge) tips 5 seconds heat-up time

#### > ESD-SAFE



#PowerfulTogether



### SCOPE OF SUPPLY

WT1M Power Unit, 230V  
WTMT MSTweezers, 80 W, 24V  
RTWMS 030 K MicroTips (2 x 40 W)  
WSR 211 Safety Rest with Stop & Go Function

### TECHNICAL DATA SOLDERING STATION WT 1M

Dimensions L x W x H (mm) 150 x 130 x 101  
Dimensions L x W x H (inch) 5.91 x 5.12 x 3.98

Fuse 230V (mA) T1

Weight approx. (kg) 1,9

Mains supply voltage (V/Hz)  
230 / 50  
120 / 60  
100 / 50/60

Power consumption (W) 95

Safety class I, antistatic housing  
III, Soldering tool

Temperature range / Tool dependent  
°C 50 - 450 / 550  
°F 150-850 / 950

Temperature accuracy (°C/°F) ± 9 / ± 17

Temperature stability (°C/°F) ± 2 / ± 4

Subject to technical alterations and amendments.

### TECHNICAL DATA WTMT MS MICRO TWEEZERS

Temperature range °C 100 - 450  
Temperature range °F 200 - 850

Power consumption 80 W (2 x 40 W)

Mains supply voltage (V/Hz) 12V / AC

Heat-up time (50°C to 350°C) (120°F to 660°F) 5 sec.

Safety rest WSR 211

Tip type series RTWMS / RTWPS

Supply unit WT 1M, WT 2M, WR 3M

Subject to technical alterations and amendments.