



WT2023M 2 CHANNEL REWORK KIT, 150 W, 230 V

ORDER NO: T0053462699

COMPACT. POWERFUL. VERSATILE.
BOOST YOUR PRODUCTIVITY

Discover the WT 2M Soldering Station, your ultimate productivity partner.

With extremely fast heat-up and recovery times, it handles all tasks effortlessly. No more juggling tools or compromising performance – just reliable versatility and unmatched value. Choose worry-free precision and unstoppable productivity. Choose Weller WT Soldering Stations.

+ KEY FEATURES

- > **2 CHANNEL REWORK KIT (150 W)**
to cover micro and standard soldering and desoldering tasks including WTMP MS Micro pencil and WTMT MS Micro tweezers with active (cartridge) tip technology
- > **RTM AND RTW TIP FAMILY**
5 seconds heat-up time
- > **HIGH PRODUCTIVITY**
- > **INTUITIVE USE**
thanks to clear menu structure
- > **REDUCED FOOTPRINT**
thanks to stackability
- > **GRAPHICAL BACKLIT LC-DISPLAY**
- > **HIGH PERFORMANCE AND FUNCTIONALITY**
many connectable tools
- > **HOUSING COVER**
useable as storage
- > **OFF TIME, PROCESS WINDOW,**
Lock function, Offset Stackable units
- > **CONNECTABLE TO**
ZeroSmog Fume Extraction Units
- > **STATION SET**
to cover smallest to standard rework tasks
- > **MICRO DESOLDERING TOOLS**
with active (cartridge) tips 5 seconds heat-up time
- > **STACKABLE UNITS**
- > **CONNECTABLE**
to ZeroSmog Fume Extraction Units
- > **ESD-SAFE**



#PowerfulTogether

weller-tools.com

Weller® is a registered trademark of Apex Brands, Inc. © 2024 | Specifications subject to change without notice.



[More information](#)

SCOPE OF SUPPLY
WT2M Power Unit, 230V WTMP MS Micro Soldering Iron, 40 W, 12V RTM 013 S MS Micro Soldering Tip WSR 205 Safety Rest with Stop & Go Function WTMT MS Micro/Nano Tweezers, 80 W, 12V RTWMS 030 K Micro Tips (2 x 40 W) WSR 11 Safety Rest with Stop & Go Function

TECHNICAL DATA SOLDERING STATION WT 2M
Dimensions L x W x H (mm) 150.0 x 130.0 x 101.0mm Dimensions L x W x H (inch) 5.91 x 5.43 x 3.98
Fuse T0,8
Weight approx. (kg) 1,9
Mains supply voltage (V/Hz) 230 / 50 120 / 60 100 / 50/60
Power consumption (W) 150 W
Safety class I, antistatic housing III, Soldering tool
Temperature range / Tool dependent 50 - 450 / 550 °C 150-850 / 950 °F
Temperature accuracy ± 9 °C / ± 17 °F
Temperature stability (°C/°F) ± 2 / ± 4
Subject to technical alterations and amendments.

TECHNICAL DATA	SOLDERING IRON WTMP MS	TWEETTER WTMT MS MS
Temperature range	°C 100 - 450	°C 100 - 450
Temperature range	°F 200 - 950	°F 200 - 950
Power consumption	40 W (55 W)	80 W (2x40 W)
Mains supply voltage (V/Hz)	12V / AC	12V / AC
Heat-up time (50°C to 350°C) (120°F to 660°F)	5 sec.	5 sec.
Safety rest	WSR 205	WSR 211
Tip type series	RTM MS	RTWMS / RTWPS
Supply unit	WT 1M, WT 2M, WR 3M	WT 1M, WT 2M, WR 3M
Subject to technical alterations and amendments.		